

T estpassport Q&A



La meilleure qualité le meilleur service

<http://www.testpassport.fr>

Service de mise à jour gratuit pendant un an

Exam : 642-035

**Title : Troubleshooting Cisco Data
Center Unified Computing**

Version : DEMO

1.Refer to the exhibit. A server has a service profile that is configured to boot over iSCSI. During boot, this message is displayed. What is the cause of this message?

```
EFI Shell version 2.31 [4.654]
Current running mode 1.1.2
Device mapping table
  blk0 :Removable BlockDevice - Alias (null)
        PciRoot(0x0)/Pci(0x1,0x0)/Pci(0x0,0x0)/Ctrl(0x0)/Scsi(0x0,0x0)

Press ESC in 1 seconds to skip startup.nsh, any other key to continue.
Shell> _
```

- A. The local disk is not present.
- B. RAID 0 is not configured on the local disk.
- C. The remote disk is powered off.
- D. The server has not configured the pWWN properly in the boot policy.

Answer: C

2.When using the Cisco UCS Manager GUI to troubleshoot a suspected bad memory, which logs contain data that are related to the faulty DIMM?

- A. the System Event log and Faults log that are located under the Admin tab
- B. the Events log and Faults log that are located under the Admin tab
- C. the System Event log that is located under the Server tab in the Navigation panel and the Faults log that is located under the Admin tab
- D. the System Event log that is located under the Equipment tab and the Faults log that is located under the Admin tab

Answer: D

3.Which is the cause of the disk being unavailable, during the installation of ESXi on a CSeries UCS server the logical 4TB disk for the installation client?

- A. The logical drive was created using the Embedded Software Raid Controller
- B. VMware requires the LSI Drivers to be installed first
- C. The logical drive is in RAID0
- D. The logical drive is not available as RAID has not completed building

Answer: A

4.Which of these does not have an FSM associated with it?

- A. vCenter connection
- B. service profile
- C. server hardware
- D. service profile templates

Answer: D

5.What is the default number of dynamic vNICs that is specified by the Cisco UCS Manager when creating a dynamic vNIC connection policy?

- A. 54
- B. 128
- C. 256
- D. 257

Answer: A