

T estpassport Q&A



La meilleure qualité le meilleur service

<http://www.testpassport.fr>

Service de mise à jour gratuit pendant un an

Exam : JN0-340

**Title : Juniper Networks Certified
Internet Associate, J-series
(JNCIA-J)**

Version : Demo

1. A stateful firewall on a J-series router is applied to which interface?

- A. WAN interface
- B. Trusted interface
- C. Loopback interface
- D. Untrusted interfaace

Answer: D

2. The built-in service module on a J-series router supports which two service types? (Choose two.)

- A. NAT
- B. L2TP
- C. IPSEC
- D. SSL VPN

Answer:AC

3. A J-series router can classify packets using which three methods? (Choose three.)

- A. Evil bit
- B. 802.1P
- C. IP DSCP
- D. MLPPP bundle
- E. Multifield classifier

Answer: BCE

4. Which J-Web menu is used to view the current NAT pools being used on the router?

- A. Monitor -> NAT
- B. Manage -> NAT
- C. Diagnose -> NAT
- D. Configuration -> NAT

Answer:A

5. Which two statements accurately reflect the operation of a packet filter on a J-series router? (Choose two.)

- A. It maintains protocol state
- B. It does not maintain protocol state
- C. It processes packets independently of a particular flow
- D. It processes packets within the context of a particular flow

Answer: BC

6. When configuring an IPSec tunnel on a J-series router, which two options are required? (Choose two.)

- A. IKE secret key
- B. Encryption algorithm
- C. Remote tunnel hostname
- D. Remote tunnel endpoint address

Answer:AD

7. The use of NAT can break the operation of protocols which signal dynamic port numbers within the packet flow. Which technology can be used in a NAT configuration to solve this problem?

- A. Stateful firewall
- B. Intrusion detection
- C. Port address translation
- D. Application layer gateways

Answer: D

8. Which J-series router process is responsible for performing autoinstallation?

- A. rpd
- B. dhcpcd
- C. autod
- D. slarpd

Answer: C

9. How do you disable the autoinstallation functionality on a J-series router?

- A. Return the router to the factory default configuration
- B. Reboot the router using the removable PCMCIA flash
- C. Remove the autoinstallation configuration from the router
- D. Compress the configuration button for more than 5 seconds

Answer: C

10. The router is attempting to perform autoinstallation using interface fe-0/0/0 , but has had three unsuccessful attempts. What is the next step it performs?

- A. It shuts down all of its interfaces
- B. It activates DHCP in server mode
- C. It waits 30 seconds and then tries again
- D. It reboots itself and attempts autoinstallion again

Answer: B

11. You are in the Configuration -> Quick Configuration -> Set Up menu of the J-Web application. Which two fields must be filled in before the router will commit any changes? (Choose two).

- A. Hostname
- B. Root password
- C. DNS name server
- D. Loopback address

Answer: AB

12. What is one way to activate the rescue configuration on a J-series router?

- A. Issue the load rescue command
- B. Issue the activate rescue command
- C. Press the rescue button for less than 5 seconds
- D. Press the configuration button for less than 5 seconds

Answer: D

13. Which of the following loads a factory default configuration onto your router if you do not have access to the router CLI?

- A. Press the power button for less than 5 seconds
- B. Press the power button for more than 5 seconds
- C. Press the configuration button for less than 5 seconds
- D. Press the configuration button for more than 5 seconds

Answer: D

14. Within the J-Web initial setup wizard, which menu is used to configure community and trap group information for the router?

- A. Users
- B. Set Up
- C. SNMP
- D. Interfaces

Answer: C

15. Autoinstallation supports which three options for obtaining configuration information? (Choose three.)

- A. ILMI
- B. RARP
- C. DHCP
- D. SNMP
- E. SLARP

Answer: BCE

16. Which command configures a minimal SNMP configuration?

- A. edit snmp community juniper
- B. set snmp server 10.12.1.1 version 2c
- C. set snmp community juniper authorization read-only
- D. snmp community juniper authorization read-only

Answer: C

17. Which CLI command can assist you with configuration syntax?

- A. help cli
- B. help topic
- C. help apropos
- D. help reference

Answer: D

18. Which CLI command activates your configuration changes on the router?

- A. save
- B. commit C. set run config
- D. copy start run

Answer: B

19. Which two statements regarding the JUNOS software user authentication methods are correct?
(Choose two.)

- A. All users must be configured locally on the router
- B. Multiple authentication methods can be configured
- C. Only one authentication method can be configured
- D. Multiple users can authenticate using a common local user account

Answer: BD

20. How is the J-Web interface accessed?

- A. Using telnet
- B. Using SSH
- C. Using rlogin
- D. Using HTTP
- E. Using gopher

Answer: D