estpassport Q&A



La meilleure qualité le meilleur service

http://www.testpassport.fr Service de mise à jour gratuit pendant un an **Exam**: JN0-363

Title : Service Provider Routing

and Switching, Specialist

(JNCIS-SP)

Version: DEMO

- 1. Which BGP attribute Is used to detect touting loops?
- A. AS path
- B. MED
- C. local preference
- D. next hop

Answer: A

- 2. What is the correct order of BGP attributes for active route selection?
- A. next hop -> local preference -> AS path -> MED -> origin
- B. next hop -> AS path -> local preference -> origin -> MED
- C. next hop -> local preference -> AS path -> origin -> MED
- D. next hop -> origin -> local preference -> AS path -> MED

Answer: C

- 3. Which new field is added to an IPv6 header as compared lo IPv4?
- A. version
- B. checksum
- C. fragment offset
- D. flow label

Answer: D

- 4. How does a Junos device learn about MAC addresses when II is first connected to an Ethernet LAN?
- A. The device sends out a network broadcast message asking tor all devices and MAC addresses on the network and stores this information In addition to the interface from which the response was received.
- B. The device learns the destination MAC addresses from traffic in the network and stores this MAC address in addition to the interface from which the traffic was received.
- C. The device learns the source MAC addresses from traffic in the network and stores this MAC address in addition to the interface from which the traffic was received.
- D. The device sends out a network multicast message asking for all devices and MAC addresses on the network and stores this Information in addition to the interface from which the response was received.

Answer: C

- 5. Which LSA type does an OSPF ABR use to advertise external routes generated by an NSSAASBR into the backbone?
- A. Type 5
- B. Type 7
- C. Type 3
- D. Type 1

Answer: B