Testpassport Q&A

La meilleure qualité le meilleur service

http://www.testpassport.fr

Service de mise à jour gratuit pendant un an

Exam : **JN0-647**

Title : Enterprise Routing and Switching Exam

Version : DEMO

1.Your network provider supports multicast traffic but your provider network does not. You want to allow multicast hosts outside of your network to receive multicast traffic sourced within your network.
How would you satisfy this requirement?
A. Use MSDP peering with your provider.
B. Use AutoVPN to connect to the remote hosts.
C. Use an MP-BGP session toyour provider to pass multicast traffic.
D. Use automatic multicast tunnel gateway at the edge of your network.
Answer: D

2.Click the exhibit.

```
[edit class-of-service schedulers]
user@router# show
s-1 {
        transmit-rate percent 30;
        priority high;
}
s-2 {
       transmit -rate percent 5;
       priority medium-high;
}
s-3 {
      transmit-rate percent 30;
      priority medium-low;
}
s-4 {
      transmit-rate percent 35;
      priority low;
}
```

Referring to the exhibit, traffic handled by the s-1 scheduler is out of profile.
Assuming bandwidth is available in this scenario, which statement is correct?
A. Traffic handled by the s-1 scheduler is serviced immediately after traffic being serviced by the s-4 scheduler.
B. Traffic handled by the s-1 scheduler is serviced immediately before traffic being serviced by the s-4 scheduler.
C. Traffic handled by the s-1 scheduler is serviced immediately before traffic being serviced by the s-2

scheduler.
D. Traffic handled by the s-1 scheduler is serviced immediately after traffic being serviced by the s-2 scheduler.
Answer: D

3.Click the Exhibit.

```
user@switch> show configuration protocols mvrp
interface all;

user@switch> show configuration interfaces
ge-0/0/1 {
   unit 0 {
       family ethernet-switching {
           port-mode trunk;
           vlan {
              members [vlan-308 vlan-312];
           }
      }
   }
}
ge-0/0/2 {
   unit 0 {
      family ethernet-switching {
          port-mode trunk;
     }
   }
}
ge-0/1/0 {
   unit 0 {
      family ethernet-switching {
          port-mode access;
          vlan {
             members vlan-300;
          }
      }
   }
}
ge-0/1/1 {
   unit 0 {
      family Ethernet-switching {
          vlan {
            members vlan -300;
          }
     }
   }
}
ae0 {
```

```
    unit 0{
       family Ethernet-switching {
           port-mode trunk;
           vlan {
             members [vlan-300 vlan 308];
            }
      }
    }
}
ae1 {
     unit 0 {
         family ethernet-switching {
            port-mode trunk:
         }
    }
}
```

Referring to the exhibit, which set of interfaces will be registered by MVRP?
A. ge-0/1/0, ge-0/1/1, ae0, ae1
B. ge-0/1/0, ge-0/0/2, ae0, ae1
C. ge-0/0/1, ge-0/1/1, ae0, ae1
D. ge-0/0/1, ge-0/0/2, ae0, ae1
Answer: D

4.Click the Exhibit.

```
[edit]
user@router1# show protocols bgp
group to-router2 {
    type internal;
    local-as 65512;
    neighbor 192.168.1.2 {
        peer-as 65512;
    }
}

[edit]
user@router1# show routing -options
```

```
[edit]
user@router1# run show bgp summary
Groups: 1 Peers: 1 Down peers: 1
Table      Tot Paths    Act Paths    Suppressed   History   Damp State
      Pending
inet. 0          0             0            0        0           0
Peer              AS         inPkt       OutPkt     OutQ    Flaps Last
Up/Dwn State | #Active/ Received/ Accepted/ Damped…
192.168.1.2               65512         0       6     0             0
       7: 58 Active
```

[edit]
user@router1# run show log messages
Jun 13 16:29:42 router1 flowd_octeon_ hm: pconn_client_connect: Failed to connect to the server after 0 retries
Jun 13 16:29:44 router1 rpd [3348]: bgp_recv: peer 192.168.1.2 (Internal AS 65512) : received unexpected EOF
Jun 13 16:29:47 router1 flowd_octeon_ hm: pconn_client_connect: Failed to connect to the server after 0 retries
Jun 13 16:29:57 router1 las time message repeated 2 times
Jun 13 16:30:00 router1 cron [3383] : (root) CMD (newsyslog)
Jun 13 16:30:00 router1 cron [3384] : (root) CMD (/user/libexec/atrun)
Jun 13 16:30:02 router1 flowd_octeon_ hm: pconn_client_connect: Failed to connect to the server after 0 retries
Jun 13 16:30:07 router1 flowd_octeon_hm: pconn_client_connect: Failed to connect to the server after 0 retries
Jun 13 16:30:12 router1 flowd_octeon_hm: pconn_client_connect: Failed to connect to the server after 0 retries
Jun 13 16:30:16 router1 rpd [3348]: bgp_recv: peer 192.168.1.2 (Internal AS 65512) : received unexpected EOF
Jun 13 16:30:17 router1 flowd_octeon_hm: pconn_client_connect: Failed to connect to the server after 0 retries
Jun 13 16:30: 32 router1 last message repeated 3 times
Jun 13 16:30:37 router1 flowd_octeon_hm: pconn_client_connect: Failed to connect to the server after 0 retries
Jun 13 16:30:40 router1 rpd [3348]: bgp_listen_accept: Connection attempt from unconfigured neighbor: 172.17.20.2+62931
Jun 13 16:30:42 router1 flowd_octeon_hm: pconn_client_connect: Failed to connect to connect to the server after 0 retries
Jun 13 16:30:52 router1 last message repeated 2 times
Jun 13 16:30:57 router1 flowd_octeon_hm: pconn_client_connect: Failed to connect to connect to the server after 0 retries
Jun 13 16:31:02 router1 flowd_octeon_hm: pconn_client_connect: Failed to connect to connect to the server after 0 retries
Jun 13 16:31:12 router1 last message repeated 2 times

```
[edit]
user@router2# show protocols bgp
group to-router1 {
    type internal;
    family inet {
      unicast;
    }
     neighbor 192.168.1.1;
}


[edit]
user@router2# show routing –options
autonomous-system 65512;

[edit]
user@router2# run show bgp summary
Groups: 1 Peers: 1 Down peers: 1
Table          Tot  Paths          Act Paths        Suppressed        History        Damp State
    Pending
inet. 0                0                0                 0                 0                 0

Peer                                AS       inPkt     OutPkt            OutQ            Flaps Last
Up/Dwn State | #Active/ Received/ Accepted/ Damped…
192.168.1.1                 65512          0          12                0                0
        20: 11 Active
```

You are configuring a new BGP session between router1 and router2. The session does not establish. Referring to the exhibit, what must be done to establish this session?

A. You must define the peer-as number on router2.

B. You must define the autonomous- system number under the [edit routing-options] hierarchy on router1.

C. You must specify type as external on both devices.

D. You must specify the local-address on bothdevices.

Answer: D

5.Which router ID is correct for OSFPv3?

A. 0.0.0.0

B. 2001:123:6::1

C. ::172.16.1.1

D. 172.16.1.1

Answer: A